


FLAT-LIGHT „28“



DETAILS

- + Serie: LED framylight®, beleuchtet
- + Systemtechnik Steckrahmen
- + Minimale Einbautiefe 1-seitig: 28 mm mit Verglasung
- + Minimale Einbautiefe 2-seitig: 56 mm mit Verglasung
- + Absolut wartungsfreie LED Technik
- + Hohe Energieeffizienz bei sehr geringer Wärmeentwicklung
- + Extrem lange Lebensdauer bei sehr geringem Energieverbrauch
- + Dimmbar (auf Anfrage)
- + RGB Farbwechsel (auf Anfrage)
- + Anwendungen: Innenbereich, Wandmontage, Wandeinbau, Modulsystem

+ Scheibenmaße: max. 1200 x 4000 mm
 + Leuchtfarbe: 3.200 - 3.500 Kelvin, 5.800 – 6.500 Kelvin
 + Spannung: 12 Volt
 + Leistung: ca. 0,067 A / pro LED

+ series: LED framylight®, illuminated
 + frontloading system technology
 + minimum installation depth 1-sided: 28 mm with glazing
 + minimum installation depth 2-sided: 56 mm with glazing
 + absolute maintenance-free LED
 + high energy-efficiency with minimal heat generation
 + extrem long lifetime with extra low energy use
 + dimmable (on request)
 + RGB colour change (on request)
 + applications: indoors, wall-fitted, wall recessing, modular system

+ plate dimensions: 1.200 x 4.000 mm
 + light colour: 3.200 - 3.500 Kelvin, 5.800 – 6.500 Kelvin
 + voltage: 12 volt
 + output: approx. 0,067 A / board



FLAT LIGHT „40“



DETAILS

- + Serie: LED framylight®, beleuchtet
- + Systemtechnik rahmenlos
- + Minimale Einbautiefe 1-seitig: 40 mm rahmenlos
- + Minimale Einbautiefe 2-seitig: 90 mm rahmenlos
- + Absolut wartungsfreie SMD LED Technik mit 6.000 K
- + Hohe Energieeffizienz bei sehr geringer Wärmeentwicklung
- + Extrem lange Lebensdauer bei sehr geringem Energieverbrauch
- + Dimmbar (auf Anfrage)
- + RGB Farbwechsel (auf Anfrage)
- + Anwendungen: Innenbereich, Wandmontage, Wandeinbau, Modulsystem

+ Scheibenmaße: max. 1200 x 4000 mm
 + Leuchtfarbe: 3200 - 3500 Kelvin, 5800 – 6500 Kelvin
 + Spannung: 12 Volt
 + Leistung: ca. 0,067 A / pro LED

+ series: LED framylight®, illuminated
 + frameless system technology
 + minimum installation depth 1-sided: 40 mm frameless
 + minimum installation depth 2-sided: 90 mm frameless
 + absolute maintenance-free SMD LED technology with 6000 K
 + high energy-efficiency with minimal heat generation
 + extrem long lifetime with extra low energy use
 + dimmable (on request)
 + RGB colour change (on request)
 + applications: indoors, wall-fitted, wall recessing, modular system

+ plate dimensions: 1.200 x 4.000 mm
 + light colour: 3200 - 3.500 Kelvin, 5.800 – 6.500 Kelvin
 + voltage: 12 volt
 + output: approx. 0,067 A / board

